CERTIFICATE

No. Z2 11 02 21860 130

Holder of Certificate: Ledon A/S

> Vestergade 25 Gram

6510 Gram **DENMARK**

Certification Mark:



Product: Chutes

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 71382967-01

Valid until: 2016-02-07

Date, 2011-02-09

Page 1 of 2

(Jens Biesenack)



CERTIFICATE No. Z2 11 02 21860 130

Model(s):

Tunnel chutes

Parameters:

Spiral slide

Rostrum height: 4,50 m Tower distance: 2,50 m Sliding surface: 7,40 m

S-design

Rostrum height: 3,60 m Tower distance: 6,75 m Sliding surface: 7,28 m

Straight line

Rostrum height: 3,90 m Tower distance: 7,00 m Sliding surface: 7,42 m

Straight line with 90° Rostrum height: 3,75 m Tower distance: 1,25 m Sliding surface: 7,36 m

Straight line with 45° Rostrum height: 3,80 m Tower distance: 6,40 m Sliding surface: 7,43 m

Slides consisting of components:

- 35 cm straight
- 59 cm straight (with or without polycarbonate-window)
- 106 cm straight (with or without polycarbonate-window)
- 106 cm straight as a T-shaped crawling-tube (with or without polycarbonate-window)
- 32 cm curve
- 38 cm curve
- 45 cm curve
- Ramp

The diameter of the plastic slides is 77 cm and the wall thickness is approx. 6 mm - 8 mm.

Tested according to: EN 1176-1:2008 EN 1176-3:2008 DIN EN 1176-1:2008 DIN EN 1176-3:2008

Production Facility(ies):

21860

Page 2 of 2

