

## Maintenance instructions DecoMark®:

- Prefabricated thermoplastic product
- Product thickness max. 2 mm
- Friction: Initial value 65/55 SRT (See also the Warranty section)
- Colour fastness: Maximum change in  $\Delta E$  50 (See also the Warranty section)
- Does not contain environmentally harmful substances

### Maintenance for general outdoor dirt:

- Sweeping machine with nylon brushes
- Snow clearance and salting can be carried out as normal, but steel and metal blades on snow ploughs should be avoided
- Clean the material using a high pressure washer with a minimum of 250 bar and approx. 80° hot water
- Cleaning is recommended every six months under normal use

### Maintenance for heavy dirt:

- Graffiti, oil or skid marks: high pressure hosing or shot blasting, depending on the amount of dirt
- Chewing gum: there is no universally known method other than attempting with high pressure hosing or shot blasting

### Repairing by damage, vandalism and wear:

- When burning on new material in order to repair an old marking in case of damage, vandalism and/or wear, then a colour difference must be expected between the new material and the old material.

## Warranty DecoMark®:

The colour fastness of the product is guaranteed with a maximum change of ( $\Delta E$ ) 50 (colour change based on spectrophotometer readings) after the initial gloss of the product has disappeared.

The friction of the product is guaranteed with an initial value of 65 SRT to 55 SRT (skid resistance tester value) in accordance with EN1436 Appendix.

The warranty does not cover damage sustained as a result of vandalism, abnormal use, lack of maintenance, heavy-handed cleaning and snow clearance, or ordinary wear and tear. Nor does it cover damage to the works that can be ascribed to faults in underlying layers.

Installations must be carried out by according to the instructions in the box.